



lighting

- Robe 250AT Profile
- Robe 250AT Wash
- 500 / 650W Profile wide angle zoom
- 500 / 650W Fresnel
- 1kw Fresnel
- 2kW Fresnel
- Par 64 CP62 1kW
- Source 4 Par 575w (WFL)
- * refocusable lantern
- 203 gel number (Rosco E Colour)
- #67 gel number (Rosco Supergel)

key

- scaffolding upright
- scaffolding at grid height
- - - scaffolding waist and knee rails
- black drape
- openable black drape on track
- FOH display board
- internal poster wall/drape
- limit of playing area
- no scenic pieces downstage of this line
- escape route sign (maintained)
- downlighter (maintained)

rostra/steeldeck heights

- steeldeck/step @ 360mm
- steeldeck/step @ 720mm
- steeldeck/step @ 1080mm
- steeldeck/step @ 1440mm
- steeldeck/step @ 1800mm
- steeldeck/step @ 2160mm (intermediate steps every 180mm)

C venues ltd accepts no liability for any inaccuracies
This plan is provisional and subject to change

For further information please contact C venues on
+44 (0)845 260 1030 or email production@cvenues.com

Copyright © C venues ltd – plan updated 30 June 2010

Cvenue level +3
end-on theatre space

Scale
0 1m