



lighting

- Robe 250AT Profile
- Robe 250AT Wash
- 650W Profile wide angle zoom
- 650W Fresnel
- 2kW Fresnel
- Source Par MFL 575W
- Par 64 CP62 1kW
- Par 64 EXG 1kW
- centre stage special (fixed)
- refocusable lantern
- light can be re-gelled
- gel number (Rosco E-color/Lee Filters)
- gel number (Rosco Supergel)
- by arrangement, these channels can be made available for repatching

key

- escape route sign (maintained)
- bulkhead (maintained)
- bulkhead (non-maintained)
- housetlight
- working light (white)
- working light (blue)
- fittings/furniture
- internal screen/display board
- truss
- scaffolding at grid height
- scaffolding handrail
- scaffolding upright
- solid barrier ground to 900mm
- black drape
- openable black drape on track
- black drape header

rostra/steps/steeldeck heights

- + 180mm
- + 360mm
- + 540mm
- + 720mm
- + 900mm
- + 1080mm
- + 1260mm
- + 1440mm

C venues ltd accepts no liability for any inaccuracies
This plan is provisional and subject to change

For further information please contact C venues on
+44 (0)845 260 1030 or email production@cvenues.com

Copyright © C venues ltd – plan updated 1 July 2011



Ceca Main Theatre (E26)
Festival Fringe Venue