



- key**
- escape route sign (maintained)
 - bulkhead (maintained)
 - bulkhead (non-maintained)
 - black drape from grid to floor
 - black drape from under control gallery deck/desk level to floor
 - black drape from grid to control gallery deck/desk level
 - ladderbeam at grid height
 - scaffolding bar at grid height
 - non-structural scaffolding bar at grid height (note: typical positions shown – non-structural bars may be re-configured)
 - pillar 200mm diameter (300mm at base and top)

lighting

- Moving light (spot)
- Moving light (wash)
- 500 / 650W Profile wide angle zoom
- 500 / 650W Fresnel
- Par 64 CP62 1kW
- Par 64 EXG 1kW
- * refocusable lantern
- 203 gel number (Rosco E Colour)
- #367 gel number (Rosco Supergel)
- 71-80** by arrangement, these channels can be made available for repatching

**steeldeck/
rostra heights**

- +918
- +765
- +612
- +459
- +306
- +15

C venues Ltd accepts no liability for any inaccuracies
This plan is provisional and subject to change

For further information please contact C venues on
+44 (0)845 260 1000 or email production@cvenues.com

Copyright © C venues Ltd – plan updated 9 June 2010

Stage height approx 3.9m to lowest point of grid
Room height approx 4.25m to acoustic ceiling